

# Pfenniger SA


Maquinaria, Insumos y Servicios Industriales desde 1928  
[www.pfenniger.com](http://www.pfenniger.com)

## Monitoreo y Análisis de fluidos



## +GF+ SIGNET Metal Installation Fittings


### Iron Threaded Tees with NPT Threads



Part no.	Size	NPT	L	H
IR4T010	1.00 in.	1.0	3.5	4.2
IR4T012	1.25 in.	1.25	4.0	4.5
IR4T015	1.50 in.	1.50	4.75	4.7
IR4T020	2.00 in.	2.0	5.0	5.2

- PVDF insert - all sizes
- Mounts on SCH 40 metal pipe


### Iron Strap-on Saddles



Part no.	Size	H	o.d. min	o.d. max	C
IR8S020	2.00 in.	5.5	2.35	2.56	1.438
IR8S025	2.50 in.	5.5	2.44	2.91	1.438
IR8S030	3.00 in.	6.5	2.97	3.54	1.438
IR8S040	4.00 in.	7.5	3.74	4.55	1.438
IR8S050	5.00 in.	9.0	4.74	5.63	2.25
IR8S060	6.00 in.	10.5	5.94	6.70	2.25
IR8S080	8.00 in.	12.0	7.69	8.72	2.25
IR8S100	10.0 in.	18.0	10.64	12.12	2.25
IR8S120	12.0 in.	20.0	12.62	14.32	2.25

- C - Clearance dimension
- Up to 8 in. - PVDF insert, over 8 in. - PVC

### Copper/Bronze Sweat-on Tee



Part no.	Size	L	H	i.d.
CUKT005	0.50 in.	3.20	3.50	0.631
CUKT007	0.75 in.	3.00	3.65	0.831
CUKT010	1.00 in.	3.20	3.81	1.132
CUKT012	1.25 in.	4.1	4.10	1.382
CUKT015	1.50 in.	4.2	4.30	1.633
CUKT020	2.00 in.	4.95	4.90	2.133

- No insert up to 1 in., over 1 in. - PVDF
- Mounts on copper pipe

### Copper/Bronze Braze-on Brazolets




Part no.	Size	W	H	C
BR4B025	2.5 in.	2.50	2.96	1.438
BR4B030	3.0 in.	2.55	2.90	1.438
BR4B040	4.0 in.	2.50	2.75	1.438
BR4B050	5.0 in.	3.50	3.98	2.25
BR4B060	6.0 in.	3.50	4.00	2.25
BR4B080	8.0 in.	3.50	4.00	2.25
BR4B100	10.0 in.	3.50	4.00	2.25
BR4B120	12.0 in.	3.50	7.00	2.25

- C - Clearance dimension
- Up to 8 in. - PVDF insert, over 8 in. - PVC insert
- Mounts on copper pipe

## +GF+ SIGNET Metal Installation Fittings

### Carbon Steel Threaded Tees w/NPT Threads



Part no.	Size (NPT)	L	H
CS4T005	0.50 in.	3.6	4.0
CS4T007	0.75 in.	3.6	4.2
CS4T010	1.00 in.	3.6	4.2
CS4T012	1.25 in.	3.8	4.5
CS4T015	1.50 in.	4.1	4.8
CS4T020	2.00 in.	4.9	5.3

- PVDF insert - all sizes
- Mounts on SCH 40 metal pipe


### Carbon Steel Weld-on Weldolets



Part no.	Size	H	W	C
CS4W025	2.50 in.	2.96	2.50	1.438
CS4W030	3.00 in.	2.90	2.55	1.438
CS4W040	4.00 in.	2.75	2.50	1.438
CS4W050	5.00 in.	3.98	3.50	2.25
CS4W060	6.00 in.	4.00	3.50	2.25
CS4W080	8.00 in.	4.00	3.50	2.25
CS4W100	10.0 in.	4.00	3.50	2.25
CS4W120	12.0 in.	7.00	3.50	2.25

- Up to 8 in. - PVDF insert, over 8 in. - PVC
- Mounts on SCH 40 metal pipe (Special order over 12 in.)
- C - Clearance dimension


### 316 SS Threaded Tees with NPT Threads



Part no.	Size (NPT)	L	H
CR4T005	0.50 in.	3.6	4.0
CR4T007	0.75 in.	3.6	4.2
CR4T010	1.00 in.	3.6	4.2
CR4T012	1.25 in.	3.8	4.5
CR4T015	1.50 in.	4.1	4.8
CR4T020	2.00 in.	4.9	5.3

- PVDF insert - all sizes
- Mounts on SCH 40 metal pipe

### 316 SS Weld-on Weldolets




Part no.	Size	H	W	C
CR4W025	2.50 in.	2.96	2.50	1.438
CR4W030	3.00 in.	2.90	2.55	1.438
CR4W040	4.00 in.	2.50	2.75	1.438
CR4W050	5.00 in.	3.98	3.50	2.25
CR4W060	6.00 in.	4.00	3.50	2.25
CR4W080	8.00 in.	4.00	3.50	2.25
CR4W100	10.0 in.	4.00	3.50	2.25
CR4W120	12.0 in.	7.00	3.50	2.25

- Up to 8 in. - PVDF insert, over 8 in. - PVC
- Mounts on SCH 40 metal pipe
- C - Clearance dimension

## +GF+ SIGNET Metal Installation Fittings

### Metalex Strap-On Saddle



Part no.	Size	H	W	o.d. min	o.d. max
P526-1020	2.00 in.	7.0	5.5	2.35	2.56
P526-1025	2.50 in.	7.0	5.5	2.44	2.91
P526-1030	3.00 in.	7.5	6.0	2.97	3.54
P526-1040	4.00 in.	8.0	7.0	3.74	4.55
P526-1050	5.00 in.	10.0	8.0	4.74	5.63
P526-1060	6.00 in.	10.5	9.5	5.94	6.70
P526-1080	8.00 in.	12.75	12.0	7.69	8.72
P526-1100	10.0 in.	14.5	15.0	10.64	12.12
P526-1120	12.0 in.	17.0	17.0	12.62	14.32

### Metalex Socket Weld Mini-Tap



Part no.	Size	L	H	W	i.d.
P526-2005	0.50 in.	2.0	3.0	2.4	0.850
P526-2007	0.75 in.	2.0	3.0	2.4	1.060
P526-2010	1.00 in.	2.0	3.0	2.4	1.325

### Metalex Weld-On Mini-Tap



Part no.	Size	H	W
P526-2012	1.25 in.	2.25	1.66
P526-2015	1.50 in.	2.20	1.66
P526-2020	2.00 in.	2.17	1.66
P526-2025	2.50 in.	2.10	1.66
P526-2030	3.00 in.	2.0	1.66
P526-2040	4.00 in.	1.95	1.66
P526-2050	5.00 in.	1.83	1.66
P526-2060	6.00 in.	1.75	1.66
P526-2080	8.00 in.	1.56	1.66
P526-2100	10.0 in.	1.35	1.66
P526-2120	12.0 in.	1.15	1.66

C = 1.062 in., Sensor clearance dimension

# Pfenniger SA

Maquinaria, Insumos y Servicios  
Industriales desde 1928  
[www.pfenniger.com](http://www.pfenniger.com)

El Totoral 601-D / Quilicura  
Fono +56-2-733 5320 / Fax +56-2-733 5098  
Casilla 2827, Correo 21, Santiago  
[mailbox@psa.cl](mailto:mailbox@psa.cl)